FUNCTIONAL SAFETY

CERTIFICATE

CERTIFICATO – ZERTIFIKAT – CERTIFICADO – CERTIFICAT

The product:

Seismic Velocity Transmitter ST5484E
Vibration Transmitter ST5491E (All configurations)

Manufactured by:

Metrix Instruments Co.
18824 Fallbrook Dr. Houston, TX 77064
United States of America

suitable for the following safety function(s):

To provide a 4-20mA DC signal output proportional to the vibration amplitude of rotating equipment portion where installed

has been assessed per the relevant requirements of

IEC 61508:2010 Parts 1 to 2

and meets the requirements providing the following:

Systematic Capability: The compliance with the requirements for the avoidance of systematic faults and the requirements for the control of systematic faults have been achieved following the compliance Route 1_S.	SC 2
Hardware Safety Integrity: The constraints on hardware safety integrity have been verified in order to achieve a sufficiently robust architecture taking into account the level of element and subsystem complexity following the compliance Routes 1_H and 2_H.	Type A
Random Safety Integrity: The estimated safety integrity, for each safety function, due to random hardware safe and dangerous failures rates (excluding "no part" and "no effect" contribution).	See page 2

The architectural constraints and the effects of random failures (PFH/PFD_{AVG}) must be verified for each specific application and safety function implemented by the E/E/PE safety-related system.

Certified by:

BYHON

BYHON Certification Director:

Rosati Francesco

CERTIFICATE No:
MTXI-5484E-ENS-B01

Issued:
May 23rd, 2025

Valid until:
May 22nd, 2028

The owner of a valid certificate for an assessed product is authorized to affix the following mark to all recognized devices which are identical to the product assessed.

BYHON SIL

ANAB
ANSI National Accreditation Board
ACCREDITED
ISO/IEC 17065
PRODUCT CERTIFICATION BODY
#8914

The design of each Safety Instrumented Function (SIF) shall meet the requirements listed in the reference standards that shall be selected by taking into account the specific application. Specific activities necessary to investigate and reach a judgment on the adequacy of the functional safety achieved by the E/E/PE safety-related system or compliant items (elements/subsystems) has been conducted by an independent assessor.

The following failure rates data shall be used to the PFH/PFD_{AVG} estimation, taking into consideration all parameters such as redundancy, architectural constraints, diagnostic capability, also introduced by the whole system, including the considerations about the proof test and its effectiveness, mean time of restoration, up to the maintenance capability and its minimum characteristics.

Failure rate for ST5484E and ST5491E - All configurations

Product	Series	λ_S	λ_{DU}	λ_{DD}
Seismic Velocity Transmitter	ST5484E	94	117	114
Vibration Transmitter	ST5491E			

Note:

- All failure fates are in FIT (Failure In Time 1 FIT = 1 failure / 10^9 hours).
- The prescriptions contained in the safety manual QP064-42 shall be followed.
- The device can be used in SIL 2 application with HFT=0. In any case, the SIL reached by the entire Safety Instrumented Function (SIF) must be verified by the System Integrator / Final User considering demand mode, architectures, proof test interval and effectiveness, availability of diagnostics.

CERTIFICATE NO:
MTXI-5484E-ENS-B01

Issued:
May 23rd, 2025

Valid until:
May 22nd, 2028

The Functional Safety Assessment report no.

25-MTX-5484E-FSA-01

dated:
May 23rd, 2025

is an integral part of this certificate

Mod_12_CB Rev09

BYHON
Via Lepanto 23, 59100
Prato (PO)
ITALY